


Leveraging proprietary technology, the **EZ-RO 375/16G** system uses Reverse Osmosis (RO) to reduce Total Dissolved Solids (TDS); it provides up to 375 gal/day (1,419 L/day)* and includes a 16-gallon (60.6 L) hydropneumatic tank. Ideal for applications where RO is necessary to meet manufacturer's warranty requirements†.

Combi ovens

Steamers

Proofers

Meets combi oven and steamer
equipment water quality standards;
reduce scale and
corrosion problems due to high TDS, water



For Pentair Everpure Product Warranties visit:
<http://pentair.com/assets/foodservice-warranty>

For Pentair Patent Information visit:
<http://pentair.com/patents>

United States | " J aU | A' Uo | "9%l o; UZ%A ;E' | " " g' PEAU " J %E | sY; o; UkaU x; EapUsi C | "i l cY; Uo; x; EapUsi C
Australia | " J l E% ' Uo; | " %c; El E±' l aa' p; | " " aYaU%
China | " 5" A ac' Z A%Kp' | " " %±' % | " China | " d; A; s' E% % U x; EapUsi C
India | " l aA o% ! " " a' 5A l U d; o; U | " sá U | " K l % " | " d; A; E c' % aYá C | U x; EapUsi C
Europe | " Z; EapUq % U | " A pC | p | " ; EcaYaU | x% Aq | AYá | d; | A l C Ya% ! " 9; U EapU | " | " A pC | " | " d; A; Y% Y | o; UkaU | aU x; s l C
Japan | " C% % ; Es | " 9% ; C l á J K l A ±' 5 | " 9% ; C l á J p l U Aa ~ % % C | " % Y | " | " D% % % % | " C% % | " | " d; A; E l | o; UkaU s l A
Southeast Asia | " 9% A sA | l % | " | " D E ± Y " | Eá | " E ± % d U | " | " | " d; A; sY; o; UkaU x; EapUsi C

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners.