


## SYSTEM DESCRIPTION

Leveraging proprietary technology, the  system uses Reverse Osmosis (RO) to reduce Total Dissolved Solids (TDS); it provides up to 200 gal/day (757 L/day)\* and includes a two-gallon (7.6) hydropneumatic tank. Blending and remineralization allow you to



" J a U | A' U p | " 9% f | o | U Z % A ; E' " " " g' P E A U " J % F | s Y | o | U k a U x | E a U s i C | f i c Y | U s | x | E a U s i C  
 " J f E % ' U p | " % c | E i E ± " f a a' p f " " a Y a U % % " " : " d | A | % | o | U k a U x | E a U s i C  
 " 5 " A a c ' Z A % % d K P " " " % ± " % " " China | " d | A | s ' E % % % U x | E a U s i C  
 " f a A o % c ! " " a ' 5 A f U d f o | U " ~ | s a U " " K f % % " " " d | A | E c f % a Y a C | U x | E a U s i C  
 " Z | E a U q % U | A % C ! p | ; E c a Y a U | x % A q | A Y a | d | A f C Y a % % " ! " 9 | U E a A " | A % C " " d | A | Y % Y | o | U k a U | a U x | s i C  
 " C % % ; E s " 9 % " C f a J K ! A ± " 5 " " 9 % " C f a J " f U | A a " % % C " 1 % % Y " " D % % % % " " C % % " " " d | A | E f | | o | U k a U s i A  
 " " 9 % A s A | f % " " D E ± Y " | E a U | " E ± % d U " " " " d | A | s Y | o | U k a U x " " A