

## SYSTEM DESCRIPTION

Leveraging proprietary technology, the **EZ-RO 375/30ATM** system uses Reverse Osmosis (RO) to reduce Total Dissolved Solids (TDS); it provides up to 375 gal/day (1,419 L/day)\* and includes a 30-gallon (113.6 L) atmospheric tank. Ideal for applications where RO is necessary to meet manufacturer's warranty requirements<sup>†</sup>.

## APPLICATIONS

Combi ovens

Steamers

Proofers

## FEATURES • BENEFITS

Meets combi oven and steamer equipment water quality standards; AÉÍ ò È á' YÉÉŋ s%ááú çás; Ýs%á %çç' corrosion problems due to high TDS, water hardness\*, and chlorides<sup>†</sup>

4CM cartridge provides optimal mineral content for proper function of conductivity sensors on steam equipment

Sealed atmospheric storage tank provides compact capacity and electronic pump delivers optimized water to downstream equipment

Pressure gauge allows monitoring of RO ÆÁ á×ú Ýáú %çç×ú Áú ÚsÍ ÈçŋÉ

Built-in bypass, sample port and áÝ' ò%ç; ÝÝ×; | ç á× ÆÝá%çá È %çç' cartridge replacement

ZÚ ×Úŋ ááá5ŋÚ çúÈ; ;: Áú%á È' Ç; çŋ%°; šáŋ; ÁúŋÉ' ŋŋáÝ±Ú ò á' í' ò%çá; ÚŋŋÉ' È' á' | Áú ÚÇ; çŋ%á' %çç%ç' decrease product life. Also can reduce sediment and chlorine to help protect the RO membrane\*

ŋŋÉ' | í' ò' ;' ;' í' Ý; í' ×áŋçŋ | ç' ò%çá Ú line to equipment

Installation kit comes complete with ááŋŋÉ±' ááŋŋÉ±' %çççç' í' áÉáŋŋÉ±' ;' %çç' ò%çá' for installation

ŋŋÉ' | ;' šŋÉsú] P Ç; | Ç' ŋŋÉ; Ý%çá Ýá×' to two times more water than standard RO membranes<sup>†</sup>

Numerous patents pending on technology and other aspects of the product design

## INSTALLATION TIPS

Kí á×; Úí Úç %çç; á' Ýá; çí Ús; Úŋ | ç' ŋŋÉK' 5

<sup>†</sup> When installed, serviced and maintained according to Pentair Everpure Installation Operation Instructions.

<sup>†</sup> Up to 50% recovery compared to standard ] P Ýúá; Ç Ý' ò' ŋŋÉ' ;' Ú' sí' ò; Úú

+Z' ;+Ýá' ;E

Feed water connection to system—should be COLD only. Tempered water up to 80°F " š%ççŋ' áÝ; ç'

' í' Èí' á; ús; | ; ç' Ýúá; Ç' Ý'



United States |