

PLM SERIES FILTER SYSTEMS

The System:2 Mod Media PLM Series Aboveground System

Dimensions and Performance

EASYCLEAN™ D.E. FILTER SYSTEMS

D.E. Filter System comes in a variety of sizes to suit most

Ordering Information

Product	Pump THP	Pump Cord	Hose Kit

¹

² Flow Rate and Turnover Capacity based on Filter.

³ WARNING: A suitable ground fault interrupter (GFCI) should always be installed on aboveground system equipment.

Dimensions and Performance

OptiFlo Pump



See page 353 for replacement parts.

SAND DOLLAR® FILTER SYSTEMS




Sand Dollar Filter System²

Our blow-molded process creates a one piece, non-corrosive tank of outstanding strength

provides excellent performance.

Featured Highlights

- Six-position 1-1/2 in. multiport valve
- New 1.0 THP OptiFlo® Pump
- One piece, durable non-corrosive tank
- Combination water and sand drain makes servicing and winterizing fast and easy
- Unionized Pump to Filter connection



Ordering Information

Product	Pump THP	Pump Cord	Hose Kit (Ft.)	Effective Filtration Area (Sq. Ft.)	Flow ¹ Rate (GPM)	Turnover Capacity (In Gallons) ¹			Tank Diameter (In.)	Tank Height (In.)	Sand Required (Lbs.)
						8 Hour	10 Hour	12 Hour			
SAND DOLLAR FILTER SYSTEMS											
PNSD0035OE1160	1.0	Standard plug 3 ft cord	6 ft	1.4	35	16,800	21,000	25,200	16	28-1/2	100
PNSD0035OE11X0	1.0	Standard plug 3 ft cord	None	1.4	35	16,800	21,000	25,200	19	34	150
PNSD0040OE1162	1.0	Standard plug 3 ft cord	6 ft	1.8	40	19,200	24,000	28,800	19	34	150
PNSD0040OE11X0	1.0	Standard plug 3 ft cord	None	1.8	40	19,200	24,000	28,800	19	34	150
PNSD0040OE1260	1.0	Twistlock plug 3 ft cord	6 ft	1.8	40	19,200	24,000	28,800	19	34	150
PNSD0060OE1160	1.0	Standard plug 3 ft cord	6 ft	2.3	60	28,800	36,000	43,200	22	35-1/2	250
PNSD0060OE11X0	1.0	Standard plug 3 ft cord	None	2.3	60	28,800	36,000	43,200	22	35-1/2	250
PNSD0060OE1260	1.0	Twistlock plug 3 ft cord	6 ft	2.3	60	28,800	36,000	43,200	22	35-1/2	250

¹ Flow Rate and Turnover Capacity based on Filter.

² WARNING: A suitable ground fault interrupter (GFCI) should always be installed on aboveground system equipment.

Dimensions and Performance



See pages 355 for replacement parts.

Featured Highlights

- for performance.
- One-piece polyethylene tank
- Multi-port valve selector activates backwashing action with one quick turn
- Easy-to-read top-mounted pressure gauge

installation and servicing

large capacity OptiFlo Series pump. Low maintenance

